

Date: 2018/04/19

Product Data Sheet

Special Notices:

The contaminants or other substances removed or reduced by this water treatment system are not necessarily in your water.

"Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Model:

Model No KLBG005-B20

Product Name Jumbo, Lead removal Activated Carbon Block filter cartridge

Description 0.5uM, L20"(508mm), Activated Carbon Block Filter with Lead removal media,

Jumbo, DOE /drop-in type

Claiming:

- ✓ Heavy metal reduction, mainly focusing on Lead reduction
- ✓ Dirt, particles, as small as 0.5uM by mechanical means
- ✓ Chlorine, Pesticides, Hazardous, Odor & Taste reduction
- ✓ Bacteria resistance
- ✓ Scale Stop.

Features:

- Activated Carbon made from 100% premium coconut shell to bring mild taste.
- Efficiency to reduce VOCs, pesticide & hazardous chemicals.
- Materials complied with NSF/ANSI 42 requirement.

Specification:

Operation Pressure10-120psi (0.7-6.8 bar)Operation Temperature $35^{\circ}F \sim 120^{\circ}F$ $(2^{\circ}C \sim 38^{\circ}C)$

Operation Flow Rate 10 LPM

Service lifespan 180,000 L @ 85% Chlorine reduction rate

360,000 L@ 50% Chlorine reduction rate

Initial Pressure drop 0.11kgs/cm²

Initial Lead reduction rate >99%



KLBG005-B20 OD4.5" x L20"

^{*} Life span capacity is tested based on 2ppm chlorine influent with 80% reduction as life definition by Caware in-house Lab and 50% reduction by NSF42 7.3.3. All followed by the test standard NSF42 7.3.3.

^{*} The result of service lifespan and pressure drop could be varied in field.